



RVI + FOSAR

Remote Visual Inspection,
Foreign Object Search & Retrieval



SENSOR[®]
NETWORKS, INC.

Inspection, Testing & Asset-Integrity Solutions

366 Walker Drive, Suite 200 • State College, PA 16801
(814) 466-7207 • SensorNetworksInc.com

Offices in Houston, Hong Kong, and Osaka

Version 2.0

insight into your assets

What you don't know about your critical plant assets and infrastructure can develop into significant risks. Sensor Networks, Inc. delivers the visual inspection tools you need to see inside and inspect process and pressure components for cleanliness and mechanical damage; helping you assess condition and retrieve loose parts.



innovation

At Sensor Networks, we combine new technologies with novel approaches to monitoring asset integrity, giving you advanced tools to keep your systems operating safely, productively and efficiently.



reliability

More than thirty Fortune 500 companies already rely on our technology and team to gain better insight on their critical infrastructure.

expertise

Drawing on more than 90 years of combined experience in visual inspection across a range of industrial sectors, our team takes the guesswork out of applications engineering. Trust us to bring the best technologies and techniques to bear on your inspection challenges.



KOCH

ExxonMobil






Xcel Energy™



Exelon®

PTZx

PTZx includes everything you need to perform tank, vessel or large-area inspections of piping and facility infrastructure. Even with 100' of cable, cable reel, monitor and digital recorder, this system weighs under 30 lbs. (13.6 kg) and can be carried in one hand. The result of decades of RVI experience, PTZx is rugged, reliable, waterproof and easy-to-use.





integrated system




modular system

digital video recorder & monitor

- 5" TFT color LCD with sun shield
- Date/time stamp
- Uncompressed BMP image capture
- AVI video recording
- Integrated mic with on/off
- SDHC card storage up to 32GB

control unit

- 45m reel (extendable to 90m)
- Adjustable zoom lens
- Auto/manual focus
- Adjustable light intensity
- Adjustable video brightness
- Camera position memory
- Image control



applications:

- **Nuclear Power:** Reactor pressure vessel and cooling pumps, steam generator channel head, nozzle welds, fuel pool, fuel assembly, spent fuel, IWE/IWL exams.
- **Fossil Power:** FAC & MIC inspections, baffle plates, HP steam headers, tank and vessels.
- **Refining & Petrochemical:** Tray-towers, refractory- and glass-lined vessels, tanks, pipe racks, heat exchanger internals, baffle plates



lowering pole

- carbon fiber tubing
- 6' (1.8m) length each
- connect two or more
- threaded stainless ends
- locking safety screw




tank flange mount

- mounts to flanged openings 4-24" (DN150-DN600)
- clamps pole to stabilize camera at any angle
- aluminum construction




lifting hoist ring

- mounts to pole end
- attaches to safety lanyard
- lifts pole and PTZ camera using an overhead crane



PTZx can be used for quick channel-head FOSAR inspection or tube sheet viewing.

loose parts retrieval tooling



delivery devices

adjustable elbow



rubber flex joint



spring flex joint



6" (152mm) extension







3/8" (9mm) diameter flex rod, 5' (1.5m) long

5/16" (8mm) diameter flex rod, 5' (1.5m) long

1/4" (6mm) diameter flex rod, 5' (1.5m) long

3/16" (5mm) diameter flex rod, 5' (1.5m) long



RGT

JAWS 2.0™

PTZx36

PTZx12

description	motorized retrieval tool	description	motorized retrieval tool with integral HD camera and LED lights
tool head		video	
construction	stainless steel	optical/digital zoom	12X / 12X
diameter	0.82" (21 mm)	effective pixels	~380K
access required	1.0" (25 mm)	sensitivity	1.4 lux
length	11.3" (287 mm)	HFOV (wide/tele)	58°/1.7°
push point connector	10 mm	brightness adjustment	±7 steps
weight	0.7 lbs. (0.32 kg)	lighting	
jaw opening	3.2" (81 mm)	integral LED lamps	2000 lumens
jaw clamping force	25 lbs. at tip	auxiliary LED lamps	1000 lumens × 2
end effectors (3)	curved serrated, flat serrated, fork and fine	construction	
cable		head weight	6 lb (2.7 kg)
cable material	polyurethane	pressure rating	44 psi / 100' (30 m) depth
cable dia.	3/16" (4.5 mm)	cable length	up to 300' (90m)
cable length	50' (15m) with extensions	material	nickel-plated aluminum, stainless steel
power supply		portability	single case, one-hand carry
type	lithium ion rechargeable	system weight	29 lb (13.2 kg)
size	7.0×4.8×2.7"	controls	
weight	1 lb. (0.452 kg)	pan/tilt	360° continuous / ±12°
features	battery gage	image overlay	grid, reticle
		image effects	flip, negative, freeze
		home position	joystick button
display/controller		monitor/DVR	
type	12V NiMH	LCD size	5.5" (140 mm)
size	9.0×5.5×2.4"	media	SD card
weight	3.1 lbs. (1.4 kg)		
features	HD color 5" display, HDMI video output, battery gage, grip strength indicator		
camera			
	1/3" color CMOS (1920×1080 pixels)		
JAWS 2.0 ultimate kit	all contents		
	15½×25×8½", 19 lb (8.6kg)		

* Tool comes standard with one serrated jaw.

Options include a curved serrated, fork & fine, needle-nose pliers, sampling cups, hooks and manual tool adapter.

JAWS 2.0 ultimate kit

all contents



- **standard components:** JAWS 2.0 HD grabber • JAWS 2.0 HD display/controller • AC adapter/charger • operator manual • 50' (15m) power/video extension cable
- **jaws:** fork and fine • flat serrated jaws • short serrated jaws • sampling cups • curved serrated jaws • tool adapter • needle-nose jaws
- **tools:** qty. 2 (two) snare: sm, lg • qty. 2 (two) magnets: sm, lg (w/ case) • qty. 4 (four) hooks: sm, med, lg, xl
- **push poles:** qty. 10 (ten): 5'×3/16"Ø (1.5m×5mmØ) • qty. 10 (ten): 5'×1/4"Ø (1.5m×8mmØ) • qty. 10 (ten): 5'×3/8"Ø (1.5m×9mmØ) • qty. 1 (one): 5'×5/16"Ø (1.5m×8mmØ) • qty. 10 (ten): 12'×5/16"Ø (3.0m×8mmØ) • qty. 1 (one): 16'×3/16"Ø (4.0m×6mmØ) • qty. 1 (one): 16'×5/16"Ø (4.0m×8mmØ) • qty. 1 (one): 16'×3/8"Ø (4.05m×9mmØ)
- **push pole accessories:** quiver • tee handle • adjustable elbow • rubber flex joint • spring flex joint
- **misc.:** hex keys, screws, hoist lifting ring

description	motorized retrieval tool with integral HD camera and LED lights
tool head	
construction	aluminum, stainless steel
diameter	1.4" (34 mm)
access required	1.5" (38 mm)
length	7.1" (180 mm)
push point connector	push point connector
weight	10 mm
jaw opening	quick-disconnect
jaw clamping force	0.7 lbs. (0.31 kg)
end effectors (3)	25 lbs. at tip
cable	see chart below*
cable material	30,000 Rad Avg. Total Dose
cable dia.	3/16" (4.5 mm)
cable length	50' (15m) with extensions
power supply	
type	TPE
size	1/4" (6 mm)
features	50' (15m) with extensions
display/controller	
type	12V NiMH
size	9.0×5.5×2.4"
weight	3.1 lbs. (1.4 kg)
features	HD color 5" display, HDMI video output, battery gage, grip strength indicator
camera	
	1/3" color CMOS (1920×1080 pixels)
JAWS 2.0 basic kit	all contents
	14×22×8", 12 lb (5.5kg)

camera	1/3" color CMOS (1920×1080 pixels)
viewing angle	88° hor., 63° vert., 140° diag.
lighting	2 long-life LEDs, total 150 lumens

kits:

- **standard components:** JAWS 2.0 HD grabber • JAWS 2.0 HD display/controller • AC adapter/charger • operator manual • 50' (15m) power/video cable
- **jaws:** fork and fine • flat serrated jaws • short serrated jaws • sampling cups • curved serrated jaws • tool adapter • needle-nose jaws
- **tools:** qty. 2 (two) snare: sm, lg • qty. 2 (two) magnets: sm, lg (w/ case) • qty. 4 (four) hooks: sm, med, lg, xl
- **push poles:** qty. 10 (ten): 5'×3/16"Ø (1.5m×5mmØ) • qty. 10 (ten): 5'×1/4"Ø (1.5m×8mmØ) • qty. 10 (ten): 5'×3/8"Ø (1.5m×9mmØ) • qty. 10 (ten): 12'×5/16"Ø (3.0m×8mmØ) • qty. 1 (one): 16'×3/16"Ø (4.0m×6mmØ) • qty. 1 (one): 16'×5/16"Ø (4.0m×8mmØ) • qty. 1 (one): 16'×3/8"Ø (4.05m×9mmØ)
- **push pole accessories:** quiver • tee handle • adjustable elbow • rubber flex joint • spring flex joint
- **misc.:** hex keys, screws, hoist lifting ring



Inspection, Testing & Asset-Integrity Solutions

366 Walker Drive, Suite 200 • State College, PA 16801
(814) 466-7207 • Offices in Houston, Hong Kong, Osaka

Version 2.0

www.sensornetworksinc.com